

HAULER® 1200

LOADED WITH RELENTLESS FUNCTIONALITY.

The new Hauler® 1200 is equipped to tackle the burden of every job, with a rugged truck-like design perfected by Superintendents. A large bed packed full of essential functionality can easily be converted for any task. Featuring tie down locations, divider slots and a full line of affordable accessories, transporting everything from sod to small equipment has never been easier. Your work is unforgiving, let the Hauler 1200 carry the load.

LET'S WORK.®

13.5HP

KAWASAKI Gas TOW CAPACITY

1500LB

12 CU FT CARGO

BED

1200LB

LOAD Capacity





CUSHMAN HAULER® 1200









OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Flexible Tool Clamps
- L-Track Aluminum Bed System
- Tie Down D-Loops
- Weather Enclosure
- USB Outlet • 12-Volt Outlet
- · Canopy Storage Net
- Brushguard
- ROPS-Certified Ball Cage
- Weather Enclosure
- Rearview Mirror
- Color Options
- ROPS-Certified Cab
- Ladder/Hoop Rack

RAME	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO, Painted
STANDARD COLOR	Forest Green
DIMENSIONS	115 in (202 am)
OVERALL LENGTH OVERALL WIDTH	115 in (292 cm)
	49.4 in (125 cm)
OVERALL HEIGHT W/CANOPY	71 in (179 cm)
VHEEL BASE	76.8 in (195 cm)
RONT WHEEL TRACK	35 in (89 cm)
	38.5 in (98 cm)
GROUND CLEARANCE	3.5 in (9 cm)
CARGO BOX CAPACITY	12 cu ft (0.34m^3)
POWER SOURCE	4-cycle, 24.5 ci (401cc) Cylinder
ALVE TRAIN	
IORSEPOWER (KW)	Single Cylinder OHV
ELECTRICAL SYSTEM	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
	Starter/Generator, Solid-State Regulator
SATTERY (QTY/TYPE)	One 12V Maintenance Free
KEY OR PEDAL START	Pedal Start
AIR CLEANER	Dry Cartridge
UBRICATION	Pressurized Oil System
OIL FILTER	Spin-On
COOLING SYSTEM	Air Cooled
FUEL CAPACITY	6 Gallon (22.7 L) Tank
DRIVETRAIN	Continuously Variable Transmission (CVT)
RANSAXLE	Differential with Helical Gears
GEAR SELECTION	Forward-Reverse
REAR AXLE RATIO	11.42:1(Forward) 15.78:1(Reverse)
PERFORMANCE	0.0
SEATING CAPACITY	2 Person
CURB WEIGHT	980 lb (445 kg)
BED LOAD CAPACITY	800 lb (364 kg)
EHICLE LOAD CAPACITY	1200 lb (545 kg)
SPEED	14 mph ± 0.5 mph (24.1 kph ± 0.8 kph)
OWING CAPACITY	1500 lb (680 kg) max
OUTSIDE CLEARANCE CIRCLE	23.0 ft (7 m)
STEERING & SUSPE	
STEERING	Self-Compensating Rack and Pinion
RONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement